

Model **ESPIGOL-16**  
with manual variable  
opening



## Agriculture

# ESPIGOL

## *Suspended disc harrow*

The small dimensions of the **ESPIGOL** disc harrows are ideal for farmers with small fields or tractors with limited power.

Robustly built and easy to maintain, the working angle of the rear discs can be adjusted mechanically or hydraulically, allowing them to be perfectly adapted to the specific needs of each farmer.

**“The ideal solution  
for compact  
tractors and  
vineyard growers”**





Model ESPIGOL-22 with hydraulically variable working angle

#### Optional elements:

- 610 mm toothed or smooth discs
- Hydraulic opening
- Lightning kit
- V20 reflective plates

| Model             | Required power<br>HP | Machine width<br>m | Working width<br>m | Working depth<br>cm | Clearance<br>cm | No. discs | Ø discs<br>mm | Hitch category | Approximate weight<br>kg |
|-------------------|----------------------|--------------------|--------------------|---------------------|-----------------|-----------|---------------|----------------|--------------------------|
| <b>ESPIGOL-14</b> | 45-55                | 1.70               | 1.60               | 10 - 15             | 65              | 14        | 560 - 610     | 2 N            | 550                      |
| <b>ESPIGOL-16</b> | 55-60                | 1.95               | 1.85               | 10 - 15             | 65              | 16        | 560 - 610     | 2 N            | 620                      |
| <b>ESPIGOL-18</b> | 60-65                | 2.17               | 2.07               | 10 - 15             | 65              | 18        | 560 - 610     | 2 N            | 710                      |
| <b>ESPIGOL-20</b> | 65-75                | 2.43               | 2.33               | 10 - 15             | 65              | 20        | 560 - 610     | 2 N            | 815                      |
| <b>ESPIGOL-22</b> | 75-80                | 2.60               | 2.50               | 10 - 15             | 65              | 22        | 560 - 610     | 2 N            | 895                      |